

# VS-MD9500- IN Multidimensional Data Server Datasheet

## VS-MD9500-IN



### Overview

The VS-MD9500-IN multidimensional data server is developed in accordance with GA/T 1400 requirements and WA3011 protocols. The server uses GA/T 1400's cascading interface to implement cascading and inter-connection between Video and Image Information Database application platforms and receive multidimensional data. The server features high availability, strong compatibility, and is widely applicable to industries such as safety, transportation, industrial parks, etc.

### Features

- Uses GA/T 1400's A interface to connect GA/T1400-compliant collection devices and systems and receive face and vehicle data.
- Uses GA/T 1400's B, C, D interfaces to implement human, vehicle, and event related functions.
- Follows WA3011 to connect Wi-Fi and RFID collection devices and receive MAC and RFID data.

### Specifications

Capability to receive face/vehicle images	Description
Capability to receive face/vehicle images	512Mbps
Capability to forward face/vehicle images	Description

e images	
Capability to forward face/vehicle e images	1024Mbps
Capability to receive and forward face/vehicle closeup and structured data	Description
Capability to receive and forward face/vehicle closeup and structured data	500 pieces of data per second
Capability to receive and forward original face/vehicle image URLs and MAC/RFID data	Description
Capability to receive and forward original face/vehicle image URLs and MAC/RFID data	1500 pieces of data per second
<b>Hardware Parameters</b>	<b>Description</b>
AC power input interface (PSU0)	100-240V AC; 50Hz/60Hz
Expansion power module slot (PSU1)	1 x 300w power module (standard) 1+1 redundancy (optional)
Network interface	GE*3
Serial interface	1 x RS232, 1 x RS232/RS485
USB interface	4
HDD	1TB * 2
RAM	32GB
HDMI	1
VGA	1
Dimensions (W×D×H)	551mm×482mm×87mm/2U
Weight	Standard ≤12kg; maximum ≤14kg
Whole-system consumption	200W
Operating temperature	0° C-40° C (recommended: 10° C-35° C)
Operating humidity	20RH%-80RH% (noncondensing)

## Ordering Info

Product Model	Description
VS-MD9500-IN	Multi-dimensional Data Server

### Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2023-2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.