

# Network Video Recorder

## NVR201 Series



### Key Features


- Support H.264 video formats
- Support AHD, TVI, CVI, CVBS, IP cameras with adaptive access
- 4/8-channel BNC input
- Up to 5MP resolution for recording
- Support 1-ch HDMI, 1-ch VGA output at up to 1920\*1080P
- Long transmission distance over coax cable

### Specifications


Model	NVR201-04U	NVR201-08Q
Video/Audio Input		
Analog Video Input	4-ch, BNC	8-ch, BNC
IP Video Input	2-ch (only IP up to 6ch)	2-ch (only IP up to 10ch)
Supported Analog Camera Types	<b>Support AHD input:</b> 5MP@20fps 4MP@30fps 3MP@30fps 1080P@30 fps 720P@30fps <b>Support TVI input:</b> 5MP@12.5fps 3MP@18fps 1080P@30fps 720P@30fps <b>Support CVI input:</b>	<b>Support AHD input:</b> 3MP@30fps 1080P@30 fps 720P@30fps <b>Support TVI input:</b> 3MP@18fps 1080P@30fps 720P@30fps <b>Support CVI input:</b> 1080P@30fps 720P@30fps <b>Support CVBS input</b>

	1080P@30fps 720P@30fps <b>Support CVBS input</b>	
Audio Input	4-ch, RCA	
<b>Network</b>		
Incoming Bandwidth	40Mbps	
Outgoing Bandwidth	40Mbps	
Remote Users	128	
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE	
<b>Video/Audio Output</b>		
CVBS Output	/	1-ch, BNC
HDMI/VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
Recording Resolution	5MP/4MP/3MP/1080p/720p/960H/4CIF/CIF/QCIF	3MP/1080p/720p/960H/4CIF/CIF/QCIF
Frame Rate	Mainstream: 5MP@10fps 4MP@12fps 3MP@16fps 1080P@25fp 720P@30fps 960H@30fps  Sub stream: 960H/D1@16fps CIF/QCIF@25fps/30fps	Main stream: 3MP@8fps 1080p@12fps 720@30fps 960H@30fps  Sub stream: 960H/D1@12fps CIF/QCIF@25fps/30fps
Audio Output	1-ch, RCA	
Synchronous Playback	6-ch	10-ch
<b>Decoding</b>		
Decoding format	H.264	
Live View/Playback	8MP (IP)/5MP/4MP/3MP/1080p/720p/960H/4CIF/CIF/QCIF	8MP (IP)/3MP/1080p/720p/960H/4CIF/CIF/QCIF
<b>Hard Disk</b>		
SATA	1 SATA interface	
Capacity	Up to 6TB for each HDD	
<b>External Interface</b>		
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interfaces	
Serial Interface	1xRS485	
USB Interface	Rear panel: 1xUSB2.0, Front panel: 1xUSB2.0	
<b>General</b>		
Power Supply	12V DC Power Consumption: ≤ 5 W (without HDD)	
Working Environment	-10°C~+55°C (+14°F~+131°F), Humidity ≤ 90% RH (non-condensing)	
Dimensions (W×D×H)	260mm×240mm×47mm (10.2"×9.4"×1.8")	
Weight (without HDD)	≤ 1.12 Kg (2.47 lb)	

## Dimensions



## Rear Panel



### Zhejiang Uniview Technologies Co., Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2019 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\* Product specifications and availability are subject to change without notice.